

**THE MBW-SERIES MAGNETIC BACKUP WRENCHES
SIMPLEST WAY TO STOP A NUT ROTATION.
EASY TO USE AND VERSATILE**

When torquing or loosening nuts, the thin profile of the MBW Backup wrench prevents the nut on the opposite side of the stud from turning.

No hydraulic, just mechanical & HANDS FREE OPERATION
Eliminate injuries on hand and fingers.

Eliminate sparks cause from the use of slugging / striker wrenches.

Reduce time of operation and improve in productivity.



BOLTING SOLUTIONS

Nut Across Flat Range

**30 mm - 145 mm
1 1/4" - 5 3/4"**

MAGNETS EMBEDDED

creates a magnetic field and force that attracts on other ferromagnetic materials.

BI-HEXAGONAL DESIGN

provides the ultimate mixture of versatility and durability



WIDE RANGE

of metric and imperial sizes available

HIGH STRENGTH

heat treated material heavy duty.

Model	Across Flat (mm)	Across Flat (in)	Load Limits (Ft.lbs)	Load Limits (Nm)
MBW 104	30	1 1/4	2,400	3,254
MBW 107	36	1 7/16	2,500	3,390
MBW 110	41	1 5/8	3,500	4,745
MBW 113	46	1 13/16	3,500	4,745
MBW 200	50	2	4,100	5,559
MBW 203	55	2 3/16	4,200	5,694
MBW 204	57	2 1/4	4,300	5,830
MBW 206	60	2 3/8	4,300	5,830
MBW 209	65	2 9/16	4,550	6,169
MBW 212	70	2 3/4	5,600	7,592
MBW 215	75	2 15/16	6,300	8,542
MBW 302	80	3 1/8	7,000	9,491
MBW 308	85	3 1/2	7,200	9,762
MBW 311	90	3 11/16	7,300	9,897
MBW 314	95	3 7/8	9,000	12,202
MBW 400	100	4	24,000	32,539
MBW 402	105	4 1/8	24,000	32,539
MBW 404	110	4 1/4	24,000	32,539
MBW 408	115	4 1/2	25,000	33,895
MBW 410	120	4 5/8	27,000	36,607
MBW 500	130	5	27,000	36,607
MBW 506	135	5 3/8	27,000	36,607
MBW 512	145	5 3/4	28,000	37,962



SAFETY LANDYARD

eliminate falling hazards

HANDS FREE OPERATION

eliminate hand injuries



** Safety lanyards are sold separately